

## Rectangular Roll off Recycle Container Specs

(40yd with dual hooks)

**Cross Members:** 3" channel 4.1# per foot on 16" center; 2 gussets per cross member

**Main Rails:** 2" x 6" x 3/16" tubing; with solid bull nose 1 1/2" thick steel

**Cable Hook:** 1 1/2" hook integrated and welded into substructure

**Floor:** 3/16" steel plate

**Ground Wheels:** 8" dia. x 6" long with grease fitting (2 or 4 wheels)

**Nose Rollers:** 4" dia. x 6" long with recessed grease fitting

**Latches:** Lever

**Sides/Front:** 12ga steel

**Bull Nose:** 1 1/2" thick steel

**Top Rails:** 4" x 3" x 11ga tubing

**Side Ribs:** 3" x 5" channel on 38" centers

**Hinges:** Heavy duty 8" x 8" plate w/ 1-1/2" pin w/ grease fitting

**Rear Door:** 12ga metal floor ride gate w/ "debris guard" plate

**Tarp Tie Down:** Tarp rods on side, front and door

**Paint:** Primer inside and outside 2.0 mils, industrial enamel finish to 2.0

**Protective Coating:** Applied to exterior understructure for longer life

**Roof:** 3" raised roof

**Dividers:** 2 dividers with three equal compartments  
(3) 30" x 30" sliding doors located on both sides of the container, with rain guard/weather covers.

**Load Height** (distance from ground to bottom of opening): 60"

**Dual Hooks:** Cable hook and hook lift  
Swaploader 545 Extended Version